

RP-IPG382

8-Gigabit PoE + 2-SFP(1G) Industrial PoE Switch

RP-IPG382 is the highly reliable industrial PoE switch with 8-port 10/100/1000-T PoE+ and 2 1000Base-X fiber optic interfaces. It adheres to IEEE 802.3af/at PoE standards, delivering up to 30W per port for powering devices like IP cameras and access points. The switch's DIP switch configuration simplifies setup, enabling functions such as port isolation, QoS, and PoE watchdog.



With a wide power input range of 44-57VDC and redundant power design, RP-IPG382 ensures system reliability, even in challenging environments. Its fan-less, IP40-rated cabinet and DIN-rail installation capability make it ideal for industrial use. It can operate seamlessly in temperatures ranging from -40°C to 75°C and offers high-level EMI/EMC protection.

RP-IPG382 shines in heavy industrial settings like factories, transportation systems, oil and gas facilities, chemical plants, IP surveillance, and processing automation. It excels in environments that exceed commercial product specifications, making it the top choice for industrial Ethernet networking, thanks to its rugged design and versatile features.

Features


- 8*10/100/1000Base-T RJ45 PoE ports, 2*1000Base-X SFP slots
- DC 44~57V input, redundant power supply with polarity reverse/over-voltage protection
- Complies with IEEE802.3af /at PoE+ standard
- Support powerful DIP switch function: DIP 1: Port isolation; DIP 2: 250m long distance (1-4 ports); DIP 3: QoS(1-2 ports) ; DIP 4: PoE watchdog
- Support 10K Bytes Jumbo frame
- Support 4KV surge protection and ESD: Air-15kV, Contact-8kV Protection
- IP40 fan-less and Din-rail hardware design
- Operation temperature: -40°C ~ +75°C

Specifications

Standards	<ul style="list-style-type: none"> • IEEE 802.3 Ethernet • IEEE 802.3u Fast Ethernet • IEEE 802.3ab Gigabit Ethernet • IEEE 802.3x Full-Duplex Flow Control • IEEE 802.3az Energy Efficient Ethernet • IEEE 802.3af Power-Over-Ethernet • IEEE 802.3at Power Over Ethernet plus PSE
Interface	<ul style="list-style-type: none"> • 8 x 10/100/1000Base-T PoE • 2 x 1000Base-X SFP
DIP Switch	<ul style="list-style-type: none"> • Port Isolation • 250m long distance mode(1-4 ports) • QoS(1-2 ports) • PoE watchdog
Switching capacity	<ul style="list-style-type: none"> • 20G
Packet forwarding rate	<ul style="list-style-type: none"> • 29.7Mpps
MAC address table	<ul style="list-style-type: none"> • 16K
VLAN	<ul style="list-style-type: none"> • 4K
Buffer	<ul style="list-style-type: none"> • 2M
Forwarding delay	<ul style="list-style-type: none"> • <5us
Jumbo Frame	<ul style="list-style-type: none"> • Support 10Kbytes
MDX/MIDX	<ul style="list-style-type: none"> • Support
Watchdog	<ul style="list-style-type: none"> • Support
Power parameters	
Input voltage	<ul style="list-style-type: none"> • 44-57VDC, redundant power input
Input current	<ul style="list-style-type: none"> • 5.6A Max
PoE power budget	<ul style="list-style-type: none"> • Full loading without PoE ≤7.5W • PoE power budget ≤240W
Connector	<ul style="list-style-type: none"> • Removable 4-pin terminal block
Reverse polarity protection	<ul style="list-style-type: none"> • Support
Over-voltage protection	<ul style="list-style-type: none"> • Support
Mechanical structure	
LED Indicators	<ul style="list-style-type: none"> • P (Power indicator) Green • S (System status indicator) Red • 1-8 (Copper ports indicators) Green / (PoE status indicators) Yellow • 9-10 (Fiber ports indicators) Green
Case protection	<ul style="list-style-type: none"> • IP40
Installation method	<ul style="list-style-type: none"> • Din-rail
Dimension	<ul style="list-style-type: none"> • 48 x 98 x 130mm (WxHxD)

Environment	<ul style="list-style-type: none"> Operating temperature: -40°C~+75°C Storage temperature: -40°C~+85°C Operating Humidity: 5 to 95% (Non-Condensing)
EMS	<ul style="list-style-type: none"> Surge protection of power: IEC 61000-4-5 Level 3 (4KV/2KV) (8/20us) Surge protection of Ethernet ports: IEC 61000-4-5 Level 3 (4KV/2KV) (10/700us) DIP: IEC 61000-4-11 Level 3 (10V) ESD: IEC 61000-4-2 Level 4 (8K/15K)
EMI	<ul style="list-style-type: none"> FCC Part 15B Class A
Certification	<ul style="list-style-type: none"> CE/FCC/RoHS

Dimension



Ordering information

RP-IPG382 8-Gigabit PoE + 2-SFP(1G) Industrial PoE Switch