



RP-1642

Ethernet BNC-AUI Mini Transceiver

Features

- AUI D-type 15-pin male connector for host connection
- BNC connector for 10Base-2 connection
- LEDs to indicate Transmit, Link, Receive and Collision status
- SQE (Signal Quality Error) enable/disable switch

Specifications

Standards	<ul style="list-style-type: none"> • IEEE 802.3 10Base-T and 10Base2
Access Method	<ul style="list-style-type: none"> • CSMA/CD
Transmission Rate	<ul style="list-style-type: none"> • 10Mbps
Network Connector	<ul style="list-style-type: none"> • One AUI connector and one BNC connector
Media Support	<ul style="list-style-type: none"> • Thick cable AUI, BNC
Cable Limitations	<ul style="list-style-type: none"> • 10Base5: 500m • Coaxial: RG-58 A/U thin cable, up to 185m per segment
LED Indicators	<ul style="list-style-type: none"> • Transmission, Link, Collision and Receive
Environment	<ul style="list-style-type: none"> • Operating Temperature: 0°C ~ 45°C • Storage Temperature: -20°C ~ 70°C • Humidity: 10% ~ 90% (Non-Condensing)
Dimension	<ul style="list-style-type: none"> • 57 * 44 * 194 mm
Certifications	<ul style="list-style-type: none"> • FCC, CE

Ordering information

RP-1642

Ethernet BNC-AUI Mini Transceiver